

In-truck charger

P/N: T199414ACC

Copyright © 2019, FLIR Systems, Inc.

Document identity

Publ. No.: T199414ACC Commit: 60057 Language: en-US Modified: 2019-10-02 Formatted: 2019-10-02

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations.



Power system	
Charging time	2 hours from fully depleted battery
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power, connector type	 2-pole screw terminal (on incoming cable to DC-DC converter) USB-A (on outgoing cable from DC-DC converter) USB Micro-B (on in-truck charger)
DC operation	 8–50 V DC in to DC-DC converter 5V DC, 3 A max. from DC-DC converter
Environmental data	
Operating temperature range	-40°C to +85°C (-40°F to +185°F)
Storage temperature range	–40°C to +85°C (–40°F to +185°F)
Relative humidity	Operational for non-condensing humidity between 5% and 95%.
EMC	 EN61000-6-3, Emission EN61000-6-2, Immunity FCC47CFR part 15 class B NFPA requirements ISO 7637-2 Road vehicles - Electrical disturbances from conduction and coupling Part 2: Electrical transient conduction along supply lines only

٦



In-truck charger

P/N: T199414ACC

© 2019, FLIR Systems, Inc. #T199414ACC; r. 60057; en-US

Environmental data	
Bump	Operational after exposed to: 5 pulses/ in each axis/ direction (30 total) of 30g 11ms half sine profile
Vibration	Operational after exposed to: 4, 3g rms random profile. 8 hours in each axis.
Physical data	
Color	Black
Shipping information	
Packaging, type	Card board box
List of contents	 In-truck charger Screws and rivets kit USB cable DC-DC Converter Fuse Documentation
EAN-13	4743254002579
UPC-12	845188013363
Country of origin	Malaysia

Compatible with the following products:

WWW.Furkarowski w the second s